



Carbon Dioxide C-27 with Cylinder

Item No.: 211211324

Product information

For the purity the specification is: Carbon dioxide (CO2) > 99.5 % And Impurities: Carbon monoxide (CO) < 5 ppm

Nitrogen monoxide (NO) < 2 ppm Nitrogen dioxide (NO2) < 2 ppm

Sulfur compounds (S) < 1 ppm Water (H2O) < 60 ppm

For carbon dioxide (CO2) the following is valid: 1 nm3 = 1.81 kg

1 kg = 0.55 nm3 1 bar = 14.5 psi 1 nm3 = 35.3 ft3 1 kg = 2.2 lbs

Features

- Colourless, odorless and an incombustible gas
- CO2 cylinders are fitted with handwheel operated valves and an American type side connection

Benefits

- Typical in use for carbonation of beers and fizzy drinks on board Cruise ships.
- In use for potable water treatment to control acidity.
- Additionally, can be used for MAG welding.
- For your safety, the product is delivered in standard marine type exchange cylinder complete with a unique cylinder serial number.
- We offer global availability through our Global Exchange Programme.

Specification

Genera	l:	Cyli

Cylinder Type	C-27
Invent Hazard Material (IMO/EU) classification	C-22

Physical Properties:

Colour Grey

Performance Data:

Gas Capacity (m³) 27

Dimensions /Weight:

Connection (size/type)	CGA320
Diameter (mm)	229
Gross Weight (kg)	82
Height(mm)	1350
Weight (kg)	27 Net

ı	е	CI	ır	ור	C	a	ı
Г) =	+:	۵.				

Connection (inch)	CGA320 side
Filling pressure (bar)	-
Purity	> 99.5 %
Volume (I)	40

